

Pipe & Tube Supply - 501.372.6556

Catalog Page 14

SEAMLESS & WELDED STAINLESS STEEL PIPE

ASTM-A-312 / SA-312 / A-376 / SA-376

Where Applicable: MIL-P-1144 / SW-41-44M

I.P.S.	Schedule	Outside Diameter	Wall	Weight Per Ft.	Type 304	Type 304L	Type 316	Type 316L	Type 347
1/8	10	.405	.049	.1863	X	X	X	X	
	40	.405	.068	.2447	X	X	X	X	
	80	.405	.095	.3145	X	X	X	X	
1/4	10	.540	.065	.3297	X	X	X	X	
	40	.540	.088	.4248	X	X	X	X	
	80	.540	.119	.5351	X	X	X	X	
3/8	10	.675	.065	.4235	X	X	X	X	
	40	.675	.091	.5676	X	X	X	X	
	80	.675	.126	.7388	X	X	X	X	
1/2	5	.840	.065	.5380	X	X	X	X	
	10	.840	.083	.6710	X	X	X	X	
	40	.840	.109	.8510	X	X	X	X	
	80	.840	.147	1.088	X	X	X	X	
	160	.840	.187	1.304	X		X		
	XXHVY	.840	.294	1.714	X				
3/4	5	1.050	.065	.6838	X	X	X	X	
	10	1.050	.083	.8572	X	X	X	X	
	40	1.050	.113	1.131	X	X	X	X	
	80	1.050	.154	1.474	X	X	X	X	
	160	1.050	.218	1.937	X				
	XXHVY	1.050	.308	2.441	X				
1	5	1.315	.065	.8678	X	X	X	X	
	10	1.315	.109	1.404	X	X	X	X	
	40	1.315	.133	1.679	X	X	X	X	
	80	1.315	.179	2.172	X	X	X	X	
	160	1.315	.250	2.844	X				X
1-1/4	5	1.660	.065	1.107	X	X	X	X	
	10	1.660	.109	1.806	X	X	X	X	
	40	1.660	.140	2.273	X	X	X	X	
	80	1.660	.191	2.997	X	X	X	X	
	160	1.660	.250	3.765	X		X		
1-1/2	5	1.900	.065	1.274	X	X	X	X	
	10	1.900	.109	2.085	X	X	X	X	
	40	1.900	.145	2.178	X	X	X	X	
	80	1.900	.200	3.631	X	X	X	X	
	160	1.900	.281	4.859			X	X	
2	5	2.375	.065	1.604	X	X	X	X	
	10	2.375	.109	2.638	X	X	X	X	
	40	2.375	.154	3.653	X	X	X	X	
	80	2.375	.218	5.022	X	X	X	X	
	160	2.375	.343	7.444	X				
2-1/2	5	2.875	.083	2.475	X	X	X	X	
	10	2.875	.120	3.531	X	X	X	X	
	40	2.875	.203	5.793	X	X	X	X	
	80	2.875	.276	7.661	X		X	X	
	160	2.875	.375	10.01	X		X		
3	5	3.500	.083	3.029	X	X	X	X	
	10	3.500	.120	4.332	X	X	X	X	
	40	3.500	.216	7.576	X	X	X	X	
	80	3.500	.300	10.25	X		X		
	160	3.500	.438	14.32	X		X		
3-1/2	5	4.000	.083	3.472	X	X	X	X	
	10	4.000	.120	4.973	X	X	X	X	

	40	4.000	.226	9.109	X	X	X	X
	80	4.000	.318	12.51	X		X	
4	5	4.500	.083	3.915	X	X	X	X
	10	4.500	.120	5.613	X	X	X	X
	40	4.500	.237	10.79	X	X	X	X
	80	4.500	.337	14.98	X		X	
	160	4.500	.531	22.51	X			
	XXHVY	4.500	.674	27.54	X			
5	5	5.563	.109	6.349	X	X	X	X
	10	5.563	.134	7.770	X	X	X	X
	40	5.563	.258	14.62	X	X	X	X
	80	5.563	.375	20.78	X		X	
	160	5.563	.625	32.96	X			
6	5	6.625	.109	7.585	X	X	X	X
	10	6.625	.134	9.289	X	X	X	X
	40	6.625	.280	18.97	X	X	X	X
	80	6.625	.432	28.57	X		X	
	160	6.625	.718	45.30	X		X	
8	5	8.625	.109	9.914	X	X	X	X
	10	8.625	.148	13.40	X	X	X	X
	40	8.625	.322	28.55	X	X	X	X
	80	8.625	.500	43.39	X		X	
	160	8.625	.906	74.69	X			X
10	5	10.750	.134	15.19	X	X	X	X
	10	10.750	.165	18.70	X	X	X	X
	20	10.750	.250	28.04	X	X	X	X
	40	10.750	.365	40.48	X	X	X	X
	80S	10.750	.500	54.74	X	X	X	X
12	5	12.750	.156	20.98	X	X	X	X
	10	12.750	.180	24.16	X	X	X	X
	20	12.750	.250	33.38	X	X	X	X
	40S	12.750	.375	49.56	X	X	X	X
	80S	12.750	.500	65.42	X	X	X	X
14	10S	14.000	.188	27.73	X	X	X	X
	10	14.000	.250	36.71	X	X	X	X
	40S	14.000	.375	54.57	X	X	X	X
	80S	14.000	.500	72.09	X			
16	10S	16.000	.188	31.75	X	X	X	X
	10	16.000	.250	42.05	X	X	X	X
	40S	16.000	.375	62.58	X	X	X	X
	80S	16.000	.500	82.77	X	X		
18	10S	18.000	.188	35.76	X	X	X	X
	10	18.000	.250	47.39	X	X	X	X
	40S	18.000	.375	70.59	X	X	X	X
	80S	18.000	.500	93.45	X			
20	5	20.000	.188	39.78	X			
	10	20.000	.250	52.73	X	X	X	X
	40S	20.000	.375	78.60	X	X	X	X
	80S	20.000	.500	104.1	X	X		
24	10	24.000	.250	63.41	X		X	
	40S	24.000	.375	94.62	X			
	80S	24.000	.500	125.5	X			
